



## SCT1216 Series 16A SCRs



### Circuit Diagram



### Description

With high ability to withstand the shock loading of large current, SCT1216 SCRs provide high dv/dt rate with strong resistance to electromagnetic interference. They are especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc.

### Maximum Ratings:

Characteristics	Symbol	Condition	Max.	Units
Storage junction temperature range	$T_{stg}$	-	-40-150	°C
Operating junction temperature range	$T_j$	-	-40-125	°C
Repetitive peak off-state voltage( $T_j=25^\circ\text{C}$ )	$V_{DRM}$	-	1200	V
Repetitive peak reverse voltage( $T_j=25^\circ\text{C}$ )	$V_{RRM}$	-	1200	V
Average on-state current	$I_{T(AV)}$	TO-220C( $T_c=105^\circ\text{C}$ )	10	A
RMS on-state current	$I_{T(RMS)}$	TO-263( $T_c=85^\circ\text{C}$ )	16	A
Non repetitive surge peak on-state current ( $t_p=10\text{ms}$ )	$I_{TSM}$	-	200	A
$I^2t$ value for fusing ( $t_p=10\text{ms}$ )	$I^2t$	-	200	A <sup>2</sup> s
Critical rate of rise of on-state current ( $I_G=2 \times I_{GT}$ )	$di/dt$	-	50	A/ $\mu\text{s}$
Peak gate current	$I_{GM}$	-	4	A
Average gate power dissipation	$P_{G(AV)}$	-	1	W
Peak gate power	$P_{GM}$	-	5	W

**Electrical Characteristics**(T<sub>j</sub>=25°C unless otherwise specified)

Symbol	Test Condition	Value			Unit
		MIN.	TYP.	MAX.	
I <sub>GT</sub>	V <sub>D</sub> =12V R <sub>L</sub> =33Ω	-	-	40	mA
V <sub>GT</sub>		-	-	1.3	V
V <sub>GD</sub>	V <sub>D</sub> =V <sub>DRM</sub> T <sub>j</sub> =125°C R <sub>L</sub> =3.3KΩ	0.2	-	-	V
I <sub>L</sub>	I <sub>G</sub> =1.2I <sub>GT</sub>	-	-	90	mA
I <sub>H</sub>	I <sub>T</sub> =500mA	-	-	80	mA
dV/dt	V <sub>D</sub> =2/3V <sub>DRM</sub> Gate Open T <sub>j</sub> =125°C	200	-	-	V/μs


**Static Characteristics**

Symbol	Condition	Max.	Units
V <sub>TM</sub>	I <sub>T</sub> =45A t <sub>p</sub> =380μs, T <sub>j</sub> =25°C	1.55	V
I <sub>DRM</sub>	V <sub>D</sub> =V <sub>DRM</sub> V <sub>R</sub> =V <sub>RRM</sub> , T <sub>j</sub> =25°C	10	μA
I <sub>RRM</sub>	V <sub>D</sub> =V <sub>DRM</sub> V <sub>R</sub> =V <sub>RRM</sub> , T <sub>j</sub> =125°C	4	mA

**Thermal Resistances**


Symbol	Condition	Value	Units
R <sub>th(j-c)</sub>	Junction to case(AC)	TO-220C	0.85
		TO-263	1.9

**Ordering Information**



Device	Package	Shipping
SCT1216C	TO-220C	50pcs/ Tube
SCT1216E	TO-263	800pcs/ Tape
SCT1216ETR	TO-263	800pcs/ Tape


**Marking Diagram**



Where XXXXX is YYWWL


SCT1216C = Part name  
YY = Year  
WW = Week  
L = Lot Number

**Mechanical Dimensions TO-220C**



SYMBOL	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.70		0.90	0.028		0.035
C	0.45		0.60	0.018		0.024
C2	1.23		1.32	0.048		0.052
C3	2.20		2.60	0.087		0.102
D	8.90		9.90	0.350		0.390
E	9.90		10.3	0.39		0.406
F	6.30		6.90	0.248		0.272
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.39			0.13	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
$\phi$		3.6			0.14	

**Mechanical Dimensions TO-263**




SYMBOL	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.90		10.20	0.390		0.402
A1	4.95		5.10	0.195		0.201
B	14.70		15.80	0.579		0.622
C	9.40		9.60	0.370		0.378
C1	4.70		4.80	0.185		0.189
D		2.54			0.100	
D1	7.60					
E	1.20		1.40	0.047		0.055
E1	7.20					
F	0.75		0.85	0.029		0.033
G			1.75			0.069
H	4.40		4.70	0.173		0.185
J	2.30		2.70	0.091		0.106
K	0.38		0.55	0.015		0.022
L	0	0.10	0.25	0	0.004	0.010
L1	2.24		2.84	0.088		0.112
$\phi P$	1.00		1.50	0.039		0.059
M	1.25		1.35	0.049		0.053




**Technical Data**  
**Data Sheet N2210, Rev.A**




**FIG.5: Surge peak on-state current versus number of cycles**



**FIG.6: On-state characteristics (maximum values)**



**FIG.7 Relative variations of gate trigger current, holding current and latching current versus junction temperature**



**Technical Data**  
**Data Sheet N2210, Rev.A**



**DISCLAIMER:**

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..